

5. LIFTING CAPACITIES

1) R140LC-7A

(1) 4.60m(15' 1") boom, 1.90m(6' 3") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

-  : Rating over-front
-  : Rating over-side or 360 degree

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb					*3160 *6970	*3160 *6970			*2910 *6420	2370 5220	5.95 (19.5)
4.5m (15ft)	kg lb					*3330 *7340	*3330 *7340			2840 6260	1770 3900	6.90 (22.6)
3.0m (10ft)	kg lb			*5940 *13100	*5940 *13100	*4140 *9130	3530 7780	3500 7720	2180 4810	2490 5490	1530 3370	7.37 (24.2)
1.5m (5ft)	kg lb			*8030 *17700	6070 13380	*5130 *11310	3280 7230	3390 7470	2080 4590	2400 5290	1460 3220	7.45 (24.4)
Ground Line	kg lb			*8200 *18080	5840 12870	5230 11530	3120 6880	3310 7300	2010 4430	2530 5580	1530 3370	7.17 (23.5)
-1.5m (-5ft)	kg lb	*6840 *15080	*6840 *15080	*8910 *19640	5850 12900	5170 11400	3070 6770			2980 6570	1820 4010	6.48 (21.3)
-3.0m (-10ft)	kg lb	*11210 *24710	*11210 *24710	*7580 *16710	6000 13230	*5000 *11020	3140 6920			*3380 *7450	2700 5950	5.15 (16.9)

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(2) 4.60m(15' 1") boom, 2.10m(6' 11") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb					*2930 *6460	*2930 *6460			*2780 *6130	2240 4940	6.17 (20.2)
4.5m	kg					*3140	*3140	*2650	2260	2720		
1700 (15ft)	7.09 lb					*6920	*6920	*5840	4980	6000	3750	(23.3)
3.0m (10ft)	kg lb			*5510 *12150	*5510 *12150	*3950 *8710	3550 7830	*3390 *7470	2190 4830	2400 5290	1470 3240	7.54 (24.7)
Ground Line	kg lb			*8240 *18560	5830 12850	5220 11510	3110 6860	3300 7280	2000 4410	2420 5340	1460 3220	7.35 (24.1)
-1.5m (-5ft)	kg lb	*6510 *14350	*6510 *14350	*9020 *19890	5810 12810	5140 11330	5140 11330	3270 7210	1970 4340	2820 6220	1720 3790	6.68 (21.9)

(3) 4.60m(15' 1") boom, 2.50m(8' 2") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2580 *5690	1940 4300	6.69 (21.9)
4.5m (15ft)	kg lb							*2710 *5970	2290 5050	2460 5420	1520 3350	7.53 (24.7)
3.0m (10ft)	kg lb			*4670 *10300	*4670 *10300	*3570 *7970	*3570 *7870	*3140 *6920	2210 4870	2190 4830	1330 2930	7.95 (26.1)
1.5m (5ft)	kg lb			*7530 *16600	6300 13890	*4670 *10300	3330 7340	3410 7520	2100 4630	2110 4650	1260 2780	8.03 (26.3)
Ground Line	kg lb			*8620 *19000	5870 12940	5240 11550	3120 6880	3300 7280	1990 4390	2200 4850	1310 2890	7.77 (25.5)
-1.5m (-5ft)	kg lb	*5750 *12680	*5950 *12680	*9180 *20240	5780 12740	5130 11310	3030 6680	3240 7140	1950 4300	2520 5560	1520 3350	7.15 (23.5)
-3.0m (-10ft)	kg lb	*8800 *19400	*8800 *19400	*8320 *18340	5860 12920	5150 11350	3050 6720			*3250 *7170	2060 4540	6.01 (19.7)
-4.5m (-15ft)	kg lb			*5950 *13120	*5950 *13120							

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(4) 4.60m(15' 1") boom, 3.00m(9' 10") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius										At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		7.5m(25ft)		Capacity		Reach
														m(ft)
6.0m (20ft)	kg lb							*1810 *3990	*1810 *3990			*2320 *5110	1680 3700	7.25 (23.8)
4.5m (15ft)	kg lb							*2420 *5340	2330 5140			2200 4850	1340 2950	8.02 (26.3)
3.0m (10ft)	kg lb					*3050 *6720	*3050 *6720	*2790 *6150	2240 4940	*1580 *3480	1450 3200	1970 4340	1180 2600	8.41 (27.6)
1.5m (5ft)	kg lb			*6540 *14420	6520 14370	*4210 *9280	3390 7470	*3340 *7360	2110 4650	*2110 *4650	1400 3090	1910 4210	1120 2470	8.49 (27.9)
Ground Line	kg lb			*8610 *18980	5940 13100	*5230 *11530	3140 6920	3290 7250	1990 4390	*2000 *4410	1350 2980	1970 4340	1160 2560	8.25 (27.1)
-1.5m (-5ft)	kg lb	*5250 *11570	*5250 *11570	*9200 *20280	5750 12680	5110 11270	3000 6610	3210 7080	1910 4210			2220 4890	1310 2890	7.67 (25.2)
-3.0m (-10ft)	kg lb	*7680 *16930	*7680 *16930	*8740 *19270	5760 12700	5090 11220	2980 6570	3210 7080	1920 4230			2830 6240	1710 3770	6.64 (21.8)
-4.5m (-15ft)	kg lb	*11270 *24850	*11270 *24850	*7040 *15520	5950 13120	*4460 *9830	3100 6830							

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

2) R140LC-7A, 2-PIECE BOOM

(1) 4.90m(16' 1") 2-piece boom, 1.90m(6' 3") arm equipped with 0.58m³(SAE heaped) bucket and 600mm(24") triple grouser shoe and 2200kg (4830 lb) counterweight.

-  : Rating over-front
-  : Rating over-side or 360 degree

Load point height		Load radius						At max. reach		
		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
										m(ft)
6.0m (20ft)	kg lb			*2730 *6020	*2730 *6020			*2620 *5780	2030 4480	6.45 (21.2)
4.5m (15ft)	kg lb			*3070 *6770	*3070 *6770	*2920 *6440	2230 4920	2550 5620	1550 3420	7.32 (24.0)
3.0m (10ft)	kg lb	*6070 *13380	*6070 *13380	*3930 *8660	3450 7610	*3230 *7120	2140 4720	2260 4980	1350 2980	7.76 (25.5)
1.5m (5ft)	kg lb			*4920 *10850	3170 6990	3350 7390	2020 4450	2180 4810	1290 2840	7.84 (25.7)
Ground Line	kg lb	*5350 *11790	*5350 *11790	5130 11310	3000 6610	3250 7170	1930 4250	2280 5030	1350 2980	7.57 (24.8)
-1.5m (-5ft)	kg lb	*8700 *19180	5680 12520	5080 11200	2960 6530	3230 7120	1910 4210	2650 5840	1580 3480	6.93 (22.7)
-3.0m (-10ft)	kg lb	*7700 *16980	5840 12870	5170 11400	3030 6680					

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(2) 4.90m(16' 1") 2-piece boom, 2.10m(6' 11") arm equipped with 0.58m³(SAE heaped) bucket and 600mm(24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius						At max. reach		
		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
										m(ft)
6.0m (20ft)	kg lb			*2530 *5580	*2530 *5580			*2520 *5560	1920 4230	6.67 (21.9)
4.5m (15ft)	kg lb			*2890 *6370	*2890 *6370	*2790 *6150	2250 4960	2440 5380	1490 3280	7.51 (24.6)
3.0m (10ft)	kg lb	*5620 *12390	*5620 *12390	*3750 *8270	3480 7670	*3120 *6880	2150 4740	2170 4780	1290 2840	7.93 (26.0)
1.5m (5ft)	kg lb			*4770 *10520	3180 7010	3350 7390	2020 4450	2100 4630	1230 2710	8.01 (26.3)
Ground Line	kg lb	*5630 *12410	5610 12370	5120 11290	2990 6590	3240 7140	1930 4250	2190 4830	1280 2820	7.76 (25.5)
-1.5m (-5ft)	kg lb	*8800 *19400	5630 12410	5050 11130	2930 6460	3210 7080	1890 4170	2510 5530	1490 3280	7.13 (23.4)
-3.0m (-10ft)	kg lb	*7910 *17440	5770 12720	5120 11290	2990 6590					

(3) 4.90m(16' 1") 2-piece boom, 2.50m(8' 2") arm equipped with 0.58m³(SAE heaped) bucket and 600mm(24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius										At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		7.5m(25ft)		Capacity		Reach
														m(ft)
6.0m (20ft)	kg lb							*2150 *4740	*2150 *4740			*2340 *5160	1680 3700	7.17 (23.5)
4.5m (15ft)	kg lb					*2520 *5560	*2520 *5560	*2510 *5530	2290 5050			2210 4870	1330 2930	7.95 (26.1)
3.0m (10ft)	kg lb			*4770 *10520	*4770 *10520	*3400 *7500	*3400 *7500	*2880 *6350	2180 4810	*1720 *3790	1410 3110	1990 4390	1170 2580	8.35 (27.4)
1.5m (5ft)	kg lb			*6780 *14950	6010 13250	*4480 *9880	3230 7120	3370 7430	2040 4500	2310 5090	1360 3000	1920 4230	1110 2450	8.42 (27.6)
Ground Line	kg lb			*5900 *13010	5640 12430	5140 11330	3000 6610	3240 7140	1920 4230	*2100 *4630	1320 2910	2000 4410	1160 2560	8.18 (26.8)
-1.5m (-5ft)	kg lb	*4660 *10270	*4660 *10270	*8160 *17990	5590 12320	5040 11110	2910 6420	3180 7010	1870 4120			2260 4980	1320 2910	7.59 (24.9)
-3.0m (-10ft)	kg lb			*8290 *18280	5690 12540	5060 11160	2940 6480	3220 7100	1900 4190					

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

3) R140LCD-7A

(1) 4.60m(15' 1") boom, 1.9m(6' 3") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

-  : Rating over-front
-  : Rating over-side or 360 degree

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb					*3160 *6970	*3160 *6970			*2910 *6420	2510 5530	5.95 (19.5)
4.5m (15ft)	kg lb					*3330 *7340	*3330 *7340			*3000 *6610	1890 4170	6.90 (22.6)
3.0m (10ft)	kg lb			*5940 *13100	*5940 *13100	*4140 *9130	3720 8200	*3520 *7760	2310 5090	2720 6000	1630 3590	7.37 (24.2)
1.5m (5ft)	kg lb			*8030 *17700	6410 14130	*5130 *11310	3470 7650	3690 8140	2220 4890	2620 5780	1560 3440	7.45 (24.4)
Ground Line	kg lb			*8200 *18080	6180 13620	5670 12500	3310 7300	3610 7960	2140 4720	2760 6080	1640 3620	7.17 (23.5)
-1.5m (-5ft)	kg lb	*6840 *15080	*6840 *15080	*8910 *19640	6190 13650	5620 12390	3260 7190			3250 7170	1940 4280	6.48 (21.3)
-3.0m (-10ft)	kg lb	*11210 *24710	*11210 *24710	*7580 *16710	6340 13980	*5000 *11020	3330 7340			*3380 *7450	2860 6310	5.15 (16.9)

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(2) 4.60m(15' 1") boom, 2.10m(6' 11") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb					*2930 *6460	*2930 *6460			*2780 *6130	2370 5220	6.17 (20.2)
4.5m (15ft)	kg lb					*3140 *6920	*3140 *6920	*2650 *5840	2390 5270	*2880 *6350	1810 3990	7.09 (23.3)
3.0m (10ft)	kg lb			*5510 *12150	*5510 *12150	*3950 *8710	3740 8250	*3390 *7470	2320 5110	2620 5780	1570 3460	7.54 (24.7)
1.5m (5ft)	kg lb			*8230 *18140	6470 14260	*4980 *10980	3480 7670	3690 8140	2220 4890	2530 5580	1500 3310	7.62 (25.0)
Ground Line	kg lb			*8420 *18560	6170 13600	5660 12480	3300 7280	3600 7940	2130 4700	2650 5840	1570 3460	7.35 (24.1)
-1.5m (-5ft)	kg lb	*6510 *14350	*6510 *14350	*9020 *19890	6150 13560	5590 12320	3230 7120	3570 7870	2110 4650	3080 6790	1830 4030	6.68 (21.9)
-3.0m (-10ft)	kg lb	*10480 *23100	*10480 *23100	*7840 *17280	6270 13820	*5180 *11420	3290 7250			*3400 *7500	2620 5780	5.41 (17.7)

(3) 4.60m(15' 1") boom, 2.50m(8' 2") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2580 *5690	2060 4540	6.69 (21.9)
4.5m (15ft)	kg lb							*2710 *5970	2430 5360	*2670 *5890	1620 3570	7.53 (24.7)
3.0m (10ft)	kg lb			*4670 *10300	*4670 *10300	*3570 *7870	*3570 *7870	*3140 *6920	2340 5160	2400 5290	1420 3130	7.95 (26.1)
1.5m (5ft)	kg lb			*7530 *16600	6640 14640	*4670 *10300	3520 7760	*3620 *7980	2230 4920	2320 5110	1360 3000	8.03 (26.3)
Ground Line	kg lb			*8620 *19000	6210 13690	*5520 *12170	3310 7300	3590 7910	2130 4700	2420 5340	1410 3110	7.77 (25.5)
-1.5m (-5ft)	kg lb	*5750 *12680	*5750 *12680	*9180 *20240	6120 13490	5580 12300	3220 7100	3540 7800	2080 4590	2760 6080	1630 3590	7.15 (23.5)
-3.0m (-10ft)	kg lb	*8800 *19400	*8800 *19400	*8320 *18340	6200 13670	*5450 *12020	3240 7140			*3250 *7170	2190 4830	6.01 (19.7)
-4.5m (-15ft)	kg lb			*5950 *13120	*5950 *13120							

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(4) 4.60m(15' 1") boom, 3.00m(9' 10") arm equipped with 0.58m³(SAE heaped) bucket and 600mm (24") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius										At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		7.5m(25ft)		Capacity		Reach
														m(ft)
6.0m (20ft)	kg lb							*1810 *3990	*1810 *3990			*2320 *5110	1780 3920	7.25 (23.8)
4.5m (15ft)	kg lb							*2420 *5340	*2420 *5340			2400 5290	1430 3150	8.02 (26.3)
3.0m (10ft)	kg lb					*3050 *6720	*3050 *6720	*2790 *6150	2370 5220	*1580 *3480	1550 3420	2170 4780	1260 2780	8.41 (27.6)
1.5m (5ft)	kg lb			*6540 *14420	*6540 *14420	*4210 *9280	3580 7890	*3340 *7360	2240 4940	*2110 *4650	1500 3310	2100 4630	1210 2670	8.49 (27.9)
Ground Line	kg lb			*8610 *18980	6280 13850	*5230 *11530	3330 7340	3590 7910	2120 4670	*2000 *4410	1450 3200	2170 4780	1250 2760	8.25 (27.1)
-1.5m (-5ft)	kg lb	*5250 *11570	*5250 *11570	*9200 *20280	6090 13430	5560 12260	3200 7050	3510 7740	2050 4520			2440 5380	1410 3110	7.67 (25.2)
-3.0m (-10ft)	kg lb	*7680 *16930	*7680 *16930	*8740 *19270	6100 13450	5530 12190	3180 7010	3510 7740	2050 4520			3090 6810	1830 4030	6.64 (21.8)
-4.5m (-15ft)	kg lb	*11270 *24850	*11270 *24850	*7040 *15520	6290 13870	*4460 *9830	3290 7250							

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

4) R140LCM-7A

(1) 4.60m(15' 1") boom, 1.90m(6' 3") arm equipped with 0.58m³(SAE heaped) bucket and 800mm (32") triple grouser shoe and 2200kg (4830 lb) counterweight.

-  : Rating over-front
-  : Rating over-side or 360 degree

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2630 *5800	2230 4920	6.87 (22.5)
4.5m (15ft)	kg lb					*2880 *6350	*2880 *6350	*2890 *6370	2740 6040	*2730 *6020	1810 3990	7.63 (25.0)
3.0m (10ft)	kg lb			*5200 *11460	*5200 *11460	*3800 *8380	*3800 *8380	*3250 *7170	2650 5840	2580 5690	1630 3590	7.99 (26.2)
1.5m (5ft)	kg lb			*7960 *17550	7390 16290	*4880 *10760	3940 8690	*3740 *8250	2530 5580	2530 5580	1590 3510	8.01 (26.3)
Ground Line	kg lb	*3550 *7830	*3550 *7830	*8720 *19220	7030 15500	*5660 *12480	3750 8270	3890 8580	2440 5380	2670 5890	1670 3680	7.70 (25.3)
-1.5m (-5ft)	kg lb	*6180 *13620	*6180 *13620	*9150 *20170	6980 15390	*5870 *12940	3680 8110	3850 8490	2400 5290	3100 6830	1950 4300	7.00 (23.0)
-3.0m (-10ft)	kg lb	*9400 *20720	*9400 *20720	*8100 *17860	7090 15630	*5320 *11730	3720 8200			*3260 *7190	2700 5950	5.74 (18.8)

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(2) 4.60m(15' 1") boom, 2.10m(6' 11") arm equipped with 0.58m³(SAE heaped) bucket and 800mm (32") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2620 *5780	2220 4890	6.87 (22.5)
4.5m (15ft)	kg lb					*2870 *6330	*2870 *6330	*2880 *6350	2730 6020	*2720 *6000	1810 3990	7.63 (25.0)
3.0m (10ft)	kg lb			*5190 *11440	*5190 *11440	*3780 *8330	*3780 *8330	*3240 *7140	2640 5820	2580 5690	1620 3570	7.99 (26.2)
1.5m (5ft)	kg lb			*7950 *17530	7380 16270	*4870 *10740	3930 8660	*3730 *8220	2520 5560	2530 5580	1580 3480	8.01 (26.3)
Ground Line	kg lb	*3560 *7850	*3560 *7850	*8730 *19250	7020 15480	*5650 *12460	3740 8250	3870 8530	2430 5360	2670 5890	1660 3660	7.70 (25.3)
-1.5m (-5ft)	kg lb	*6190 *13650	*6190 *13650	*9130 *20130	6970 15370	*5860 *12920	3660 8070	3830 8440	2390 5270	3090 6810	1940 4280	7.00 (23.0)
-3.0m (-10ft)	kg lb	*9410 *20750	*9410 *20750	*8090 *17840	7070 15590	*5310 *11710	3700 8160			*3250 *7170	2700 5950	5.74 (18.8)

(3) 4.60m(15' 1") boom, 2.50m(8' 2") arm equipped with 0.58m³(SAE heaped) bucket and 800mm (32") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2600 *5730	2200 4850	6.87 (22.5)
4.5m (15ft)	kg lb					*2840 *6260	*2840 *6260	*2850 *6280	2710 5970	*2690 *5930	1790 3950	7.63 (25.0)
3.0m (10ft)	kg lb			*5160 *11380	*5160 *11380	*3750 *8270	*3750 *8270	*3210 *7080	2610 5750	2560 5640	1600 3530	7.99 (26.2)
1.5m (5ft)	kg lb			*7920 *17460	7350 16200	*4840 *10670	3710 8620	*3700 *8160	2500 5510	2510 5530	1560 3440	8.01 (26.3)
Ground Line	kg lb	*3580 *7890	*3580 *7890	*8750 *19290	6990 15410	*5620 *12390	3710 8180	3850 8490	2400 5290	2650 5840	1640 3620	7.70 (25.3)
-1.5m (-5ft)	kg lb	*6220 *13710	*6220 *13710	*9110 *20080	6940 15300	*5830 *12850	3640 8020	3810 8400	2370 5220	3070 6770	1920 4230	7.00 (23.0)
-3.0m (-10ft)	kg lb	*9430 *20790	*9430 *20790	*8060 *17770	7050 15540	*5280 *11640	3680 8110			*3230 *7120	2680 5910	5.74 (18.8)

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.

(4) 4.60m(15' 1") boom, 3.00m(9' 10") arm equipped with 0.58m³(SAE heaped) bucket and 800mm (32") triple grouser shoe and 2200kg (4830 lb) counterweight.

Load point height		Load radius								At max. reach		
		1.5m(5ft)		3.0m(10ft)		4.5m(15ft)		6.0m(20ft)		Capacity		Reach
												m(ft)
6.0m (20ft)	kg lb									*2550 *5620	2170 4780	6.87 (22.5)
4.5m (15ft)	kg lb					*2790 *6150	*2790 *6150	*2800 *6170	2670 5890	*2650 *5840	1750 3860	7.63 (25.0)
3.0m (10ft)	kg lb			*5100 *11240	*5100 *11240	*3700 *8160	*3700 *8160	*3160 *6970	2570 5670	2520 5560	1560 3440	7.99 (26.2)
1.5m (5ft)	kg lb			*7860 *17330	7300 16090	*4790 *10560	3860 8510	*3650 *8050	2450 5400	2470 5450	1520 3350	8.01 (26.3)
Ground Line	kg lb	*3630 *8000	*3630 *8000	*8780 *19360	6940 15300	*5560 *12260	3670 8090	3800 8380	2360 5200	2610 5750	1610 3550	7.70 (25.3)
-1.5m (-5ft)	kg lb	*6260 *13800	*6260 *13800	*9050 *19950	6880 15170	*5780 *12740	3590 7910	3760 8290	2320 5110	3040 6700	1890 4170	7.00 (23.0)
-3.0m (-10ft)	kg lb	*9470 *20880	*9470 *20880	*8000 *17640	6990 15410	*5220 *11510	3630 8000			*3190 *7030	2640 5820	5.74 (18.8)

- Note
1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the ROBEX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.
 3. The load point is a hook located on the back of the bucket.
 4. *indicates load limited by hydraulic capacity.