

9. RECOMMENDED OILS

Use only oils listed below or equivalent.

Do not mix different brand oil.

Service point	Kind of fluid	Capacity ℓ (U.S. gal)	Ambient temperature °C (°F)						
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)
Engine oil pan	Engine oil	18.5(4.9)				SAE 30			
			SAE 10W						
			SAE 10W-30						
			SAE 15W-40						
Swing drive	Grease	0.32(0.1)	NLGI NO.1						
				NLGI NO.2					
Swing drive	Gear oil	2.5(0.7)		SAE 85W-140					
Final drive		3.0 × 2 (0.8 × 2)							
Hydraulic tank	Hydraulic oil	Tank; 124(32.8)	ISO VG 32						
		System; 210(55.5)	ISO VG 46						
			ISO VG 68						
Fuel tank	Diesel fuel	270(71.0)	ASTM D975 NO.1						
			ASTM D975 NO.2						
Fitting (Grease nipple)	Grease	As required	NLGI NO.1						
			NLGI NO.2						
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	24(6.3)		Ethylene glycol base permanent type					

SAE : Society of Automotive Engineers

API : American Petroleum Institute

ISO : International Organization for Standardization

NLGI : National Lubricating Grease Institute

ASTM : American Society of Testing and Material