## TROUBLESHOOTING GUIDE

#### 1. ENGINE

# \* This guide is not intended to cover every conditions, however many of the more common possibilities are listed.

The engine oil pressure lamp lights ON when engine speed is raised after completion of warm up.  - Add the oil to the specified level.  - Replace the oil filter cartridge.  - Check oil leakage from the pipe or the joint.  - Replace the monitor.  - Steam is emitted from the top part of the radiator (the pressure valve).  - Coolant level warning lamp lights ON.  - Wash out inside of cooling system.  - Clean or repair the radiator fin.  - Check the thermostat.  - Tighten the radiator cap firmly or replace the packing of it.  - Replace the monitor.  - Add fuel.  - Repair where air is leaking into fuel system.  - Check the injection pump or the nozzle.  - Check the valve clearance.  - Check engine compression pressure.  - In cold weather, check if fuel warmer system is working normal.  - Exhaust gas is white or blue.  - Adjust to specified oil quantity.  - Replace with specified fuel.  - Check the nozzle.  - Check the nozzle.  - Check engine compression pressure.  - Check the nozzle.  - Check engine compression pressure.  - Check the nozzle.  - Check engine compression pressure.  - Check the nozzle.  - Check the nozzle.	Trouble	Service	Remark
after completion of warm up.  Check oil leakage from the pipe or the joint. Replace the monitor.  Steam is emitted from the top part of the radiator (the pressure valve). Coolant level warning lamp lights ON.  Clean or repair the radiator fin. Check the thermostat. Tighten the radiator cap firmly or replace the packing of it. Replace the monitor.  The engine does not start when the starting motor is turned over.  Check the injection pump or the nozzle. Check the valve clearance. Check engine compression pressure. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Exhaust gas occasionally turns black.  Check the nozzle. Check the nozzle. Check engine compression pressure. Check engine compression pressure. Clean or replace the air cleaner element. Check the nozzle. Check engine compression pressure. Check the nozzle. Check the nozzle. Check the nozzle. Check the nozzle.	ON when engine speed is raised	· Add the oil to the specified level.	
Check oil leakage from the pipe or the joint. Replace the monitor.  Steam is emitted from the top part of the radiator (the pressure valve). Coolant level warning lamp lights ON.  Supply the coolant and check leakage. Adjust fan belt tension. Wash out inside of cooling system. Clean or repair the radiator fin. Check the thermostat. Tighten the radiator cap firmly or replace the packing of it. Replace the monitor.  The engine does not start when the starting motor is turned over.  Check the injection pump or the nozzle. Check the valve clearance. Check engine compression pressure. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity. Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle.		· Replace the oil filter cartridge.	
Steam is emitted from the top part of the radiator (the pressure valve). Coolant level warning lamp lights ON.  Supply the coolant and check leakage.  Adjust fan belt tension.  Wash out inside of cooling system.  Clean or repair the radiator fin.  Check the thermostat.  Tighten the radiator cap firmly or replace the packing of it.  Replace the monitor.  The engine does not start when the starting motor is turned over.  Check the injection pump or the nozzle.  Check the valve clearance.  Check the valve clearance.  Check engine compression pressure.  In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity.  Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle.  Check engine compression pressure.  Clean or replace the air cleaner element.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Check oil leakage from the pipe or the joint.	
the radiator (the pressure valve). Coolant level warning lamp lights ON.  Adjust fan belt tension.  Wash out inside of cooling system.  Clean or repair the radiator fin.  Check the thermostat.  Tighten the radiator cap firmly or replace the packing of it.  Replace the monitor.  The engine does not start when the starting motor is turned over.  The engine does not start when the starting motor is turned over.  Add fuel.  Repair where air is leaking into fuel system.  Check the injection pump or the nozzle.  Check the valve clearance.  Check engine compression pressure.  In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity.  Replace with specified fuel.  Exhaust gas occasionally turns black.  Clean or replace the air cleaner element.  Check the nozzle.  Check engine compression pressure.  Check the nozzle.  Check the nozzle.		· Replace the monitor.	
Coolant level warning lamp lights ON.  - Wash out inside of cooling system Clean or repair the radiator fin Check the thermostat Tighten the radiator cap firmly or replace the packing of it Replace the monitor.  The engine does not start when the starting motor is turned over.  - Add fuel Repair where air is leaking into fuel system Check the injection pump or the nozzle Check the valve clearance Check engine compression pressure In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  - Adjust to specified oil quantity Replace with specified fuel.  Exhaust gas occasionally turns black.  - Check engine compression pressure Check the nozzle Check engine compression pressure Clean or replace the air cleaner element Check engine compression pressure Check engine compression pressure Check the nozzle Check engine compression pressure Clean or replace the turbocharger.  - Check the nozzle Check the nozzle Check the nozzle Check the nozzle.	the radiator (the pressure valve). Coolant level warning lamp lights	· Supply the coolant and check leakage.	
ON.  - Wash out inside of cooling system Clean or repair the radiator fin Check the thermostat Tighten the radiator cap firmly or replace the packing of it Replace the monitor.  - Add fuel Repair where air is leaking into fuel system Check the injection pump or the nozzle Check the valve clearance Check the valve clearance Check engine compression pressure In cold weather, check if fuel warmer system is working normal.  - Exhaust gas is white or blue Adjust to specified oil quantity Replace with specified fuel.  - Check the nozzle Check the nozzle Check engine compression pressure Check the nozzle Check the nozzle Check the nozzle Check engine compression pressure Clean or replace the turbocharger.  - Check the nozzle Check the nozzle.		· Adjust fan belt tension.	
Check the thermostat.  Tighten the radiator cap firmly or replace the packing of it.  Replace the monitor.  The engine does not start when the starting motor is turned over.  Add fuel.  Repair where air is leaking into fuel system.  Check the injection pump or the nozzle.  Check engine compression pressure.  In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity.  Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle.  Check engine compression pressure.  Check the nozzle.  Check engine compression pressure.  Check the nozzle.		· Wash out inside of cooling system.	
Tighten the radiator cap firmly or replace the packing of it.  Replace the monitor.  Add fuel.  Repair where air is leaking into fuel system.  Check the injection pump or the nozzle.  Check the valve clearance.  Check engine compression pressure.  In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity.  Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle.  Check the nozzle.  Check the nozzle.  Check engine compression pressure.  Clean or replace the air cleaner element.  Check the nozzle.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Clean or repair the radiator fin.	
packing of it.  Replace the monitor.  Add fuel.  Repair where air is leaking into fuel system.  Check the injection pump or the nozzle.  Check the valve clearance.  Check engine compression pressure.  In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity.  Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle.  Check the valve clearance.  Clean or replace the air cleaner element.  Check the nozzle.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Check the thermostat.	
The engine does not start when the starting motor is turned over.  - Add fuel.  - Repair where air is leaking into fuel system.  - Check the injection pump or the nozzle.  - Check the valve clearance.  - Check engine compression pressure.  - In cold weather, check if fuel warmer system is working normal.  - Adjust to specified oil quantity.  - Replace with specified fuel.  - Check the nozzle.  - Check the nozzle.  - Check the nozzle.  - Check engine compression pressure.  - Check the nozzle.  - Check engine compression pressure.  - Clean or replace the turbocharger.  - Combustion noise occasionally changes to breathing sound.  - Check the nozzle.			
starting motor is turned over.  Repair where air is leaking into fuel system. Check the injection pump or the nozzle. Check the valve clearance. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity. Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle. Check engine compression pressure. Check the nozzle. Check engine compression pressure. Check the nozzle.		· Replace the monitor.	
Check the injection pump or the nozzle. Check the valve clearance. Check engine compression pressure. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity. Replace with specified fuel.  Exhaust gas occasionally turns black.  Check the nozzle. Check engine compression pressure. Check engine compression pressure. Check the nozzle.	The engine does not start when the	· Add fuel.	
Check the valve clearance. Check engine compression pressure. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity. Replace with specified fuel.  Exhaust gas occasionally turns black.  Clean or replace the air cleaner element. Check the nozzle. Check engine compression pressure. Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.  Check the nozzle.	starting motor is turned over.	· Repair where air is leaking into fuel system.	
Check engine compression pressure. In cold weather, check if fuel warmer system is working normal.  Exhaust gas is white or blue.  Adjust to specified oil quantity. Replace with specified fuel.  Exhaust gas occasionally turns black.  Clean or replace the air cleaner element. Check the nozzle. Check engine compression pressure. Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Check the injection pump or the nozzle.	
<ul> <li>In cold weather, check if fuel warmer system is working normal.</li> <li>Exhaust gas is white or blue.</li> <li>Adjust to specified oil quantity.</li> <li>Replace with specified fuel.</li> <li>Exhaust gas occasionally turns black.</li> <li>Clean or replace the air cleaner element.</li> <li>Check the nozzle.</li> <li>Check engine compression pressure.</li> <li>Clean or replace the turbocharger.</li> </ul> Combustion noise occasionally changes to breathing sound.		· Check the valve clearance.	
working normal.  S-25 and 4-4.  Exhaust gas is white or blue.  Replace with specified oil quantity.  Replace with specified fuel.  Clean or replace the air cleaner element.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Check engine compression pressure.	
Replace with specified fuel.      Clean or replace the air cleaner element.     Check the nozzle.     Check engine compression pressure.     Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.  Clean or replace the turbocharger.			
Exhaust gas occasionally turns black.  Clean or replace the air cleaner element.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Clean or replace the nozzle.	Exhaust gas is white or blue.	· Adjust to specified oil quantity.	
black.  Check the nozzle.  Check engine compression pressure.  Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.		· Replace with specified fuel.	
Check the nozzle.     Check engine compression pressure.     Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.  Check the nozzle.		· Clean or replace the air cleaner element.	
Clean or replace the turbocharger.  Combustion noise occasionally changes to breathing sound.  Clean or replace the turbocharger.		· Check the nozzle.	
Combustion noise occasionally changes to breathing sound.		· Check engine compression pressure.	
changes to breathing sound.		· Clean or replace the turbocharger.	
		· Check the nozzle.	
Unusual combustion noise or · Check with specified fuel.	Unusual combustion noise or mechanical noise.	· Check with specified fuel.	
mechanical noise. · Check over-heating.		· Check over-heating.	
· Replace the muffler.		· Replace the muffler.	
· Adjust valve clearance.		· Adjust valve clearance.	

### 2. ELECTRICAL SYSTEM

Trouble	Service	Remark
Lamp does not glow brightly even when engine runs at high speed. Lamp flickers while engine runs.	Check for loose terminals and open-circuit wiring.     Adjust belt tension.	
Battery charging lamp does not go out even when engine runs at high speed.	Check the alternator.     Check and repair wiring.	
Unusual noise is emitted from the alternator.	· Check the alternator.	
Starting motor does not turn when starting switch is turned ON.	<ul> <li>Check and repair the wiring.</li> <li>Charge the battery.</li> <li>Check the starting motor.</li> <li>Check the safety relay.</li> </ul>	
The pinion of the starting motor keeps going in and out.	Charge the battery.     Check the safety relay.	
Starting motor turns the engine sluggishly.	Charge the battery.     Check the starting motor.	
The starting motor disengages before the engine starts up.	Check and repair the wiring.     Charge the battery.	
The engine warming up lamp does not go ON.	Check and repair wiring.     Check the monitor.	
The engine oil pressure lamp does not light up when engine is stationary (when the starting switch is in ON position.)	Check the monitor.     Check the caution lamp switch.	
Battery charging lamp does not light up when the engine is stationary. (when the starting switch is in ON position.)	Check the monitor.     Check and repair the wiring.	

### 3. OTHERS

Trouble	Service	Remark
Track slip out of place. Excessive wear of the sprocket.	· Adjust tension of track.	
Bucket either rises slowly or not at all.	· Add oil to specified level.	
Slow speed of travel, swing, boom, arm and bucket.	· Add oil to specified level.	
Unusual noise emitted from pump.	· Clean the hydraulic tank strainer.	
Excessive oil temperature rise of hydraulic oil.	Clean the oil cooler.  Adjust fan belt tension.	
· ·		