

4. WEIGHT

1) R210LC-7H

Item	R210LC-7H	
	kg	lb
Upperstructure assembly	8950	19730
Main frame weld assembly	2600	5730
Engine assembly	530	1170
Main pump assembly	120	265
Main control valve assembly	200	440
Swing motor assembly	250	550
Hydraulic oil tank assembly	240	530
Fuel tank assembly	200	440
Counterweight	3800	8380
Cab assembly	310	680
Lower chassis assembly	8700	19180
Track frame weld assembly	2600	5730
Swing bearing	260	570
Travel motor assembly	310	680
Turning joint	55	120
Track recoil spring and idler	270	600
Idler	170	370
Carrier roller	20	45
Track roller	40	85
Track-chain assembly(600mm standard triple grouser shoe)	1320	2910
Front attachment assembly(5.68m boom, 2.92m arm, 0.92m³ SAE heaped bucket)	4000	8820
5.68m boom assembly	1535	3380
2.92m arm assembly	710	1570
0.92m³ SAE heaped bucket	765	1690
Boom cylinder assembly	180	400
Arm cylinder assembly	290	640
Bucket cylinder assembly	175	390
Bucket control link assembly	170	370

2) R210LC-7H LONG REACH

Item	R210LC-7H LONG REACH	
	kg	lb
Upperstructure assembly	8950	19730
Main frame weld assembly	2600	5730
Engine assembly	530	1170
Main pump assembly	120	265
Main control valve assembly	200	440
Swing motor assembly	250	550
Hydraulic oil tank assembly	240	530
Fuel tank assembly	200	440
Counterweight	5300	11680
Cab assembly	310	680
Lower chassis assembly	8700	19180
Track frame weld assembly	2720	5730
Swing bearing	260	570
Travel motor assembly	310	680
Turning joint	55	120
Track recoil spring and idler	270	600
Idler	170	370
Carrier roller	20	45
Track roller	40	85
Track-chain assembly(800mm standard triple grouser shoe)	1605	3540
Front attachment assembly(8.2m boom, 6.3m arm, 0.52m³ SAE heaped bucket)	4595	10130
8.2m boom assembly	2105	4640
6.3m arm assembly	1100	2430
0.52m³ SAE heaped bucket	460	1010
Boom cylinder assembly	180	400
Arm cylinder assembly	270	600
Bucket cylinder assembly	130	290
Bucket control rod assembly	170	370