

9. RECOMMENDED OILS

Use only oils listed below or equivalent.

Do not mix different brand oil.

Service point	Kind of fluid	Capacity l (U.S. gal)	Ambient temperature °C (°F)						
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)
Engine oil pan	Engine oil	19(5.0) 24(6.3) (TIER II)					SAE 30		
						SAE 10W			
							SAE 10W-30		
							SAE 15W-40		
Swing drive	Gear oil	7.0(1.8)							
Final drive		11×2 (2.9×2, -#1214) 5.5×2 (1.5×2, #1215-)					SAE 85W-140		
Hydraulic tank	Hydraulic oil	Tank; 210(55.5) System; 320(84.5)					ISO VG 32		
							ISO VG 46		
							ISO VG 68		
Fuel tank	Diesel fuel	480(126.8)			ASTM D975 NO.1				
							ASTM D975 NO.2		
Fitting (Grease nipple)	Grease	As required			NLGI NO.1				
							NLGI NO.2		
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	50(13.2)					Ethylene glycol base permanent type		

SAE : Society of Automotive Engineers

API : American Petroleum Institute

ISO : International Organization for Standardization

NLGI : National Lubricating Grease Institute

ASTM : American Society of Testing and Material