







6. BUCKET SELECTION GUIDE


1) GENERAL BUCKET

					
0.79m³ PCSA heaped bucket	1.03m³ PCSA heaped bucket	※ 1.27m³ PCSA heaped bucket	1.50m³ PCSA heaped bucket	1.73m³ PCSA heaped bucket	1.85m³ PCSA heaped bucket

Capacity		Width		Weight	Recommendation			
					6.25m (20' 6") boom			
PCSA heaped	CECE heaped	Without side cutter	With side cutter		2.1m arm (6' 11")	2.5m arm (8' 2")	3.05m arm (10' 0")	3.6m arm (11' 10")
0.79m³ (1.03yd³)	0.70m³ (0.92yd³)	890mm (35.0")	1010mm (39.8")	740kg (1630lb)				
1.03m³ (1.35yd³)	0.90m³ (1.18yd³)	1090mm (42.9")	1210mm (47.6")	850kg (1870lb)				
※ 1.27m³ (1.66yd³)	1.10m³ (1.44yd³)	1290mm (50.8")	1410mm (55.5")	960kg (2120lb)				
1.50m³ (1.96yd³)	1.30m³ (1.70yd³)	1490mm (58.7")	1610mm (63.4")	1020kg (2250lb)				
1.73m³ (2.26yd³)	1.50m³ (1.96yd³)	1696mm (66.8")	-	1120kg (2470lb)				
1.85m³ (2.42yd³)	1.60m³ (2.09yd³)	1800mm (70.9")	-	1160kg (2560lb)				





※ : Standard bucket

 Applicable for materials with density of 2000kgf/m³ (3370lbf/yd³) or less

 Applicable for materials with density of 1600kgf/m³ (2700lbf/yd³) or less

 Applicable for materials with density of 1100kgf/m³ (1850lbf/yd³) or less

2) ROCK AND HEAVY DUTY BUCKET

			
◆ 1.07m ³ PCSA heaped bucket	◆ 1.27m ³ PCSA heaped bucket	◆ 1.46m ³ PCSA heaped bucket	1.16m ³ PCSA heaped bucket

Capacity		Width		Weight	Recommendation			
					6.25m (20' 6") boom			
PCSA heaped	CECE heaped	Without side cutter	With side cutter		2.1m arm (6' 11")	2.5m arm (8' 2")	3.05m arm (10' 0")	3.6m arm (11' 10")
◆1.07m³ (1.40yd³)	0.95m³ (1.24yd³)	1060mm (42.0")	-	1110kg (2450lb)				
◆1.27m³ (1.66yd³)	1.10m³ (1.44yd³)	1220mm (48.0")	-	1130kg (2490lb)				
◆1.46m³ (1.91yd³)	1.28m³ (1.67yd³)	1370mm (54.0")	-	1260kg (2780lb)				
1.16m³ (1.52yd³)	1.00m³ (1.31yd³)	1305mm (51.4")	-	1260kg (2780lb)				

◆ : Heavy duty bucket

: Rock bucket

 Applicable for materials with density of 2000kgf/m³ (3370lbf/yd³) or less

 Applicable for materials with density of 1600kgf/m³ (2700lbf/yd³) or less

 Applicable for materials with density of 1100kgf/m³ (1850lbf/yd³) or less