| Foreword | 0-1 |
|--------------------------------------|------|
| Before servicing this machine | 0-2 |
| EC regulation approved | 0-3 |
| Table to enter S/No and distribution | 0-4 |
| Safety labels | 0-5 |
| Machine data plate | 0-15 |
| Guide(Direction, S/No, Symbol) | 0-16 |

SAFETY HINTS

| 1-1 |
|------|
| 1-6 |
| 1-13 |
| 1-16 |
| |

SPECIFICATIONS

| 2-1 |
|------|
| 2-2 |
| 2-3 |
| 2-4 |
| 2-5 |
| 2-8 |
| 2-10 |
| 2-12 |
| 2-16 |
| |

CONTROL DEVICES

| 1. Cab devices ······ | 3-1 |
|-------------------------------|------|
| 2. Cluster ····· | 3-2 |
| 3. Switches ····· | 3-9 |
| 4. Levers and pedals | 3-14 |
| 5. Air conditioner and heater | 3-16 |
| 6. Others | 3-23 |

OPERATION

| Check before starting the engine | 1. Suggestion for new machine | 4-1 |
|---|-------------------------------------|------|
| 4. Mode selection system 4-6 | 2. Check before starting the engine | 4-2 |
| , | 3. Starting and stop the engine | 4-3 |
| 5. Operation of the working device 4-1 | 4. Mode selection system | 4-6 |
| | 5. Operation of the working device | 4-13 |

| 6. Traveling of the machine | 4-14 |
|--|------|
| 7. Efficient working method | 4-17 |
| 8. Operation in the special work sites | 4-21 |
| 9. Normal operation of excavator | 4-23 |
| 10. Attachment lowering | 4-24 |
| 11. Storage ····· | 4-25 |
| 12. RCV lever operating pattern | 4-27 |
| 13. Switching hydraulic attachment circuit | 4-28 |
| | |

TRANSPOTATION

| 1. Preparation for transportation | 5-1 |
|-----------------------------------|-----|
| 2. Dimension and weight | 5-2 |
| 3. Loading the machine | 5-4 |
| 4. Fixing the machine | 5-6 |
| 5. Loading and unloading by crane | 5-7 |

MAINTENANCE

| 1. Instruction |
|---------------------------------------|
| 2. Tightening torque 6-6 |
| 3. Fuel, coolant and lubricants 6-9 |
| 4. Maintenance check list ······ 6-11 |
| 5. Maintenance chart 6-16 |
| 6. Service instruction 6-18 |
| 7. Electrical system ····· 6-42 |
| 8. Air conditioner and heater 6-45 |

TROUBLESHOOTING GUIDE

| | 1. Engine ····· | 7-1 |
|---|----------------------------|-----|
| | 2. Electrical system ····· | 7-2 |
| 4 | 3. Others ····· | 7-3 |

3 HYDRAULIC BREAKER

| | 1. Selecting hydraulic breaker 8-1 |
|----|--|
| | 2. Circuit configuration 8-2 |
| 1 | 3. Maintenance 8-3 |
| 2 | 4. Precautions while operating the breaker \cdot 8-4 |
| 3 | 5. Quick clamp 8-6 |
| 6 | |
| 13 | INDEX |

FOREWORD

This manual contains a number of instructions and safety recommendations regarding driving, handling, lubrication, maintenance, inspection and adjustment of the excavator.

The manual is to promote safety maintenance and enhance machine performance.

Keep this manual handy and have all personnel read it periodically.

If you sell the machine, be sure to give this manual to the new owners.

This machine complies with EC directive "2006/42/EC".

1. **Read** and **understand** this manual before operating the machine.

This operator's manual may contain attachments and optional equipment that are not available in your area. Please consult your local Hyundai distributor for those items you require.

Improper operation and maintenance of this machine can be hazardous and could result in serious injury or death.

Some actions involved in operation and maintenance of the machine can cause a serious accident, if they are not done in a manner described in this manual.

The procedures and precautions given in this manual apply only to intended uses of the machine. If you use your machine for any unintended uses that are not specifically prohibited, you must be sure that it is safe for you and others. In no event should you or others engage in prohibited uses of actions as described in this manual.

- 2. **Inspect** the jobsite and **follow** the safety recommendations in the **safety hints** section before operating the machine.
- 3. Use genuine Hyundai spare parts for the replacement of parts.

We expressly point out that Hyundai will not accept any responsibility for defects resulting from nongenuine parts or non workmanlike repair.

In such cases Hyundai cannot assume liability for any damage.

Continuing improvements in the design of this machine can lead to changes in detail which may not be reflected in this manual. Consult Hyundai or your Hyundai distributor for the latest available information for your machine or for questions regarding information in this manual.

BEFORE SERVICING THIS MACHINE

It is the responsibility of the owner and all service and maintenance personnel to avoid accidents and serious injury by keeping this machine properly maintained.

It also is the responsibility of the owner and all service and maintenance personnel to avoid accidents and serious injury while servicing the machine.

No one should service or attempt to repair this machine without proper training and supervision.

All service and maintenance personnel should be thoroughly familiar with the procedures and precautions contained in this manual.

All personnel also must be aware of any federal, state, provincial or local laws or regulations covering the use and service of construction equipment.

The procedures in this manual do not supersede any requirements imposed by federal, state, provincial or local laws.

Hyundai can not anticipate every possible circumstance or environment in which this machine may be used and serviced.

All personnel must remain alert to potential hazards.

Work within your level of training and skill.

Ask your supervisor if you are uncertain about a particular task. Do not try to do too much too fast. Use your common sense.

EC REGULATION APPROVED

· Noise level (EN474-1 : 2006 and 2000/14/EC) are as followings.

LWA : 105dB(EU only)

LPA : 76dB

• The value of vibrations transmitted by the operator's seat are lower than standard value of (EN474-1 : 2006 and 2002/44/EC)




TABLE TO ENTER SERIAL NO. AND DISTRIBUTOR

| Machine Serial No. | |
|------------------------|---|
| Engine Serial No. | |
| Manufacturing year | |
| Manufacturer | Hyundai Heavy Industries co., Ltd. |
| Address | 1000, Bangeojinsunhwan-doro, Dong-Ku, Ulsan 682-792, Korea |
| Distributor for U.S.A | Hyundai Heavy Industries U.S.A, Inc |
| Address | 6100 Atlantic Boulevard Norcross GA 30071 U.S.A |
| Distributor for Europe | Hyundai Heavy Industries Europe N. V. |
| Address | Vossendal 11 2240 Geel Belgium |
| Dealer | |
| Address | |
| | |

SAFETY LABELS

1. LOCATION

Always keep these labels clean. If they are lost or damaged, attach them again or replace them with a new label.



16 Stay fix

0-5

2. DESCRIPTION


There are several specific warning labels on this machine please become familiarized with all warning labels.

Replace any safety label that is damaged, or missing.

1) AIR CLEANER FILTER(Item 1)

This warning label is positioned on the air cleaner cover.

* Periodic and proper inspection, cleaning and change of elements prolong engine life time and maintain the good performance of engine.





- 2) TURBO CHARGER COVER(Item 2) This warning label is positioned on the turbo charger cover.
- A Do not touch turbo charger or it may cause severe burn.



21070FW02

3) RADIATOR CAP(Item 3)

This warning label is positioned on the radiator.

▲ Never open the filler cap while engine running or at high coolant temperature.




14070FW03

4) FUELING(Item 4)

This warning label is positioned on the right side of fuel filler neck.

▲ Stop the engine when refueling. All lights or flames shall be kept at a safe distance while refueling.



5) BATTERY ACCIDENT(Item 5)

This warning label is positioned on the battery cover.


- ▲ Electrolyte containing sulfuric acid cause severe burns. Avoid being in contact with skin, eyes or clothes. In the event of accident flush with sufficient water, call a physician immediately.
- Maintain the electrolyte at the recommended level. Add distilled water to the battery only when starting up, never when shutting down.

With electrolyte at proper level, less space may cause the gases to be accumulated in the battery.

- A Extinguish all smoking materials and open flames before checking the battery.
- ▲ Do not use matches, lighters or torches as a light source near the battery for the probable presence of explosive gas.
- ▲ Do not allow unauthorized personnel to change the battery or to use booster cables.
- ▲ For safety from electric shock, do not battery terminals with a wet hand.
- 6) HYDRAULIC OIL LEVEL(Item 6) This warning label is positioned on the left side of hydraulic oil level.
- ▲ Place the bucket on the ground whenever servicing the hydraulic system.
- * Check oil level on the level gauge.
- * Refill the recommended hydraulic oil up to specified level if necessary.



36070FW05



21070FW07

- 7) HYDRAULIC OIL LUBRICATION(Item 7) This warning label is positioned on the right side of air breather.
- * Do not mix with different brand oils.
- A Never open the filler cap while engine running or at high coolant temperature.
- ▲ Loosen the cap slowly and release internal pressure completely.
- HIGH PRESSURE HOSE(Item 8) This warning label is positioned on the screen plate.
- ▲ Escaping fluid under pressure can penetrate the skin causing serious injury.
- * Study the service instruction in this manual before service work.



14070FW08




14070FW29

9) KEEP CLEAR(Item 11)

This warning label is positioned on the counterweight.


- ▲ To prevent serious personal injury or death keep clear of machine swing radius.
- A Do not deface or remove this label from the machine.



10) LIFTING EYE(Item 12)

This warning label is positioned on the counterweight.

▲ Do not lift the machine by using lifting eyes on the counterweight or the lifting eyes may be subject to overload causing its breaking and possible personal injury. See page 5-7 for proper lifting method of the machine.



21070FW10

11) SIDE KEEP CLEAR(Item 15)

This warning label is positioned on the side of counterweight.

- ▲ To prevent serious personal injury or death keep clear of machine swing radius.
- A Do not deface or remove this label from the machine.




21070FW13

12) STAY FIX(Item 16)

This warning label is positioned on the side cover.


- A Be sure to support the stay when the door needs to be opened.
- ▲ Be careful that the opened door may be closed by the external or natural force like strong wind.



13) SHEARING-ENGINE HOOD(Item 17)

This warning label is positioned on the engine hood.

- A Do not open the engine hood during the engine's running.
- ▲ Do not touch exhaust pipe or it may cause severe burn.



21070FW15

14) NO STEP-ENGINE HOOD(Item 18)

This warning label is positioned on the engine hood.

riangle Do not step on the engine hood.



21070FW16

15) TRANSPORTING (Item 19)

This warning label is positioned right side of upper frame.

- ▲ Study the operator's manual before transporting the machine, if provided and tie down arm and track to the carrier with lashing wire.
- \ast See page 5-6 for details.


16) CONTROL IDEOGRAM(Item 21)

This warning label is positioned in right window of the cab.

- Check the machine control pattern for conformance to pattern on this label. If not, change label to match pattern before operating machine.
- ▲ Failure to do so could result in injury or death.
- * See page 4-13 for details.







17) CONTROL IDEOGRAM-LH(Item 22)

This warning label is positioned on the LH console box.

- ▲ Check the machine control pattern for conformance to pattern on this label. If not, change label to match pattern before operating machine.
- ▲ Failure to do so could result in injury or death.
- * See page 4-13 for details.

18) CONTROL IDEOGRAM-RH(Item 23)


This warning label is positioned on the RH console box.

- ▲ Check the machine control pattern for conformance to pattern on this label. If not, change label to match pattern before operating machine.
- ▲ Failure to do so could result in injury or death.
- * See page 4-13 for details.


19) REF OPERATOR MANUAL (Item 24)

This warning label is positioned on the right side frame of the cab.


A Study the operator's manual before starting and operating machine.



36070FW20



21070FW21




21070FW22

20) MAX HEIGHT(Item 24)

This warning label is positioned on the right side frame of the cab.

▲ Serious injury or death can result from contact with electric lines.

An electric shock being received by merely coming into the vicinity of an electric lines, the minimum distance should be kept considering the supply voltage as page 1-7.




36070FW23

21) SAFETY FRONT WINDOW (Item 26)

This warning label is positioned on the both side frame of the cab.

A Be careful that the front window may be promptly closed.



21070FW24

22) ALTERNATE EXIT(Item 27)

This warning label is positioned on the inside of rear window.

- * The rear window serves us an alternate exit.
- * To remove rear window, pull the ring and push out the glass.




21070FW25

23) AIR CONDITIONER FILTER (Item 28)

This warning label is positioned on the air conditioner cover.

* Periodic and proper inspection, cleaning and change of filter prolong air conditioner life time and maintain good performance.




21070FW26

24) CONSOLE BOX TILTING(Item 31)

This warning label is positioned on the LH console box.


* Before you get off the machine be sure to tilt the LH console box.



25) SAFETY LEVER(Item 32)

This warning label is positioned on the cover safety.

▲ Before you get off the machine be sure to place the safety lever LOCKED position.



21070FW28

26) KEEP CLEAR-WORK AREA(Item 40)

This warning label is positioned on the counterweight.

- ▲ To prevent serious personal injury or death keep clear of machine swing radius.
- ▲ Do not deface or remove this label from the machine.




21070FW34

27) INTERFERENCE(Item 24)

This warning label is positioned on the right side frame of cab.

- ▲ Be careful to operate machine equipped with quick clamp or extensions.
- ▲ Bucket may hit cab or boom, boom cylinders when it reached vicinity of them.



14070FW62

28) TIE(Item 42)

This warning label is positioned on the lower frame.

- A Make sure no personal are standing close to the tow rope.
- ▲ See page 4-16 for detail.



4507A0FW02

29) ECU CONNECTOR(Item 33)

This warning label is positioned on the battery cover.

A Before carrying out any electric welding on this machine.

Pull the connector out of all electric control units.

- ▲ Connector the ground lead of the welding equipment as close to the welding point as possible.
- * See page 6-44 for detail.

30) TURBOCHARGER (Item 44)

This warning label is positioned in right window of the cab.

▲ In order to prevent turbocharger failure, please allow more than 5 minutes' cool down period(no load low idle operation) before shutting the engine off.

WARNING Before carrying out any electric welding on this machine Pull the connectors out of all electronic control units. Connect the ground lead of the welding equipment as close to the welding point as possible. Read the instructions in operator's manual for details.


7807AFW20

A CAUTION

In order to prevent turbocharger failure, please allow more than 5 minutes' cool down period(no load low idle operation) before shutting the engine off.

7807AFW20

MACHINE DATA PLATE




* The machine serial number assigned to this particular machine and should be used when requesting information or ordering service parts for this machine from your authorized HYUNDAI dealer. The machine serial number is also stamped on the frame.

GUIDE

1. DIRECTION

The direction of this manual indicate forward, backward, right and left on the standard of operator when the travel motor is in the rear and machine is on the traveling direction.




2. SERIAL NUMBER

Inform following when you order parts or the machine is out of order.


1) MACHINE SERIAL NUMBER

The numbers are located below the right window of the operator's cab.



2) ENGINE SERIAL NUMBER

The numbers are located on the engine name plate.



3. SYMBOLS

- A Important safety hint.
- riangle It indicates matters which can cause the great loss on the machine or the surroundings.
- * It indicates the useful information for operator.