

3. FUEL, COOLANT AND LUBRICANTS

1) NEW MACHINE

New machine used and filled with following lubricants.

Description	Specification
Engine oil	SAE 15W-40(API CH-4)
Hydraulic oil	ISO VG 46(SAE 10W)
Swing and travel reduction gear	SAE 85W-140(API GL-5)
Grease	Lithium base grease NLGI No. 2
Fuel	ASTM D975-No. 2
Coolant	Mixture of 50% ethylene glycol base antifreeze and 50% water.

SAE : Society of Automotive Engineers

API : American Petroleum Institute

ISO : International Organization for Standardization

NLGI : National Lubricating Grease Institute

ASTM : American Society of Testing and Material

2) RECOMMENDED OILS

Use only oils listed below or equivalent.

Do not mix different brand oil.

Service point	Kind of fluid	Capacity l (U.S. gal)	Ambient temperature °C(°F)						
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)
Engine oil pan	Engine oil	6.7(1.8)							
							SAE 30		
						SAE 10W			
						SAE 10W-30			
						SAE 15W-40			
Final drive	Gear oil	0.5×2 (0.1×2)					SAE 85W-140		
Hydraulic tank	Hydraulic oil	Tank: 37(9.8) System: 60(15.9)							
						ISO VG 32			
						ISO VG 46			
Fuel tank	Diesel fuel	40(10.5)							
						ASTM D975 NO.1			
Fitting (Grease nipple)	Grease	As required							
						NLGI NO.1			
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	5(1.3)							
							Ethylene glycol base permanent type		