

3. FUEL, COOLANT AND LUBRICANTS

1) NEW MACHINE

New machine used and filled with following lubricants.

Description	Specification
Engine oil	SAE 15W-40(API CF-4)
Hydraulic oil	ISO VG 46(SAE 10W)
Swing and travel reduction gear	SAE 85W-140(API GL-5)
Grease	Lithium base grease NLGI No. 2
Fuel	ASTM D975-No. 2
Coolant	Mixture of 50% ethylene glycol base antifreeze and 50% water.

SAE : Society of Automotive Engineers

API : American Petroleum Institute

ISO : International Organization for Standardization

NLGI : National Lubricating Grease Institute

ASTM : American Society of Testing and Material

2) RECOMMENDED OILS

Use only oils listed below or equivalent.

Do not mix different brand oil.

Service point	Kind of fluid	Capacity (U.S. gal)	Ambient temperature °C (°F)						
			-20 (-4)	-10 (14)	0 (32)	10 (50)	20 (68)	30 (86)	40 (104)
Engine oil pan	Engine oil	26.5(7.0)							
								SAE 30	
								SAE 10W	
								SAE 10W-30	
								SAE 15W-40	
Swing drive	Gear oil	6.0(1.6)							
Final drive		7.0 × 2 (1.8 × 2)						SAE 85W-140	
Hydraulic tank	Hydraulic oil	Tank; 230(61) System; 380(100)							
								ISO VG 32	
								ISO VG 46	
								ISO VG 68	
Fuel tank	Diesel fuel	520(137)							
								ASTM D975 NO.1	
								ASTM D975 NO.2	
Fitting (Grease nipple)	Grease	As required							
								NLGI NO.1	
								NLGI NO.2	
Radiator (Reservoir tank)	Mixture of antifreeze and water 50 : 50	45(12)							
								Ethylene glycol base permanent type	

SAE : Society of Automotive Engineers

API : American Petroleum Institute

ISO : International Organization for Standardization

NLGI : National Lubricating Grease Institute

ASTM : American Society of Testing and Material