







6. BUCKET SELECTION GUIDE

1) GENERAL BUCKET

					
1.15m³ SAE heaped bucket	1.46m³ SAE heaped bucket	1.62m³ SAE heaped bucket	2.10m³ SAE heaped bucket	2.32m³ SAE heaped bucket	1.86m³ SAE heaped bucket



Capacity		Width		Weight	6.5m (21' 4") boom				6.15m(20' 2") boom	8.6m(28' 3") boom
SAE heaped	CECE heaped	Without side cutter	With side cutter		2.5m arm (8' 2")	3.2m arm (10' 6")	3.9m arm (12' 10")	4.3m arm (14' 1")	2.5m arm (8' 2")	5.1m arm (16' 9")
1.15m³ (1.5yd³)	1.0m³ (1.3yd³)	1090mm (42.9")	1220mm (48.0")	1030kg (2270lb)						
1.46m³ (1.91yd³)	1.27m³ (1.66yd³)	1380mm (54.3")	1510mm (59.4")	1170kg (2580lb)						
1.62m³ (2.12yd³)	1.40m³ (1.8yd³)	1440mm (56.7")	1570mm (61.8")	1280kg (2820lb)						
1.86m³ (2.43yd³)	1.60m³ (2.1yd³)	1620mm (63.8")	1750mm (68.9")	1390kg (3060lb)						
2.10m³ (2.75yd³)	1.80m³ (2.4yd³)	1810mm (71.3")	1940mm (76.4")	1520kg (3350lb)						
2.32m³ (3.03yd³)	2.0m³ (2.6yd³)	1990mm (78.3")	2120mm (83.5")	1760kg (3880lb)						

 Applicable for materials with density of 2000kgf/m³ (3370lbf/yd³) or less

 Applicable for materials with density of 1600kgf/m³ (2700lbf/yd³) or less

 Applicable for materials with density of 1100kgf/m³ (1850lbf/yd³) or less

2) ROCK AND HEAVY DUTY BUCKET

	
◆ 1.62m³ SAE heaped bucket	⊙ 1.44m³ SAE ※ ⊙ 1.62m³ SAE ⊙ 1.86m³ SAE heaped bucket

Capacity		Width		Weight	Recommendation				6.15m (20' 2") boom
					6.5m (21' 4") boom				
SAE heaped	CECE heaped	Without side cutter	With side cutter		2.5m arm (8' 2")	3.2m arm (10' 6")	3.9m arm (12' 10")	4.3m arm (14' 1")	2.5m arm (8' 2")
◆1.62m³ (2.12yd³)	1.40m³ (1.8yd³)	1540mm (60.6")	-	1570kg (3460lb)					
⊙1.44m³ (1.88yd³)	1.27m³ (1.66yd³)	1280mm (50.4")	-	1565kg (3450lb)					
※⊙1.62m³ (2.12yd³)	1.40m³ (1.8yd³)	1545mm (60.8")	-	1610kg (3550lb)					
⊙1.86m³ (2.43yd³)	1.60m³ (2.1yd³)	1725mm (67.9")	-	1710kg (3770lb)					

※ : Standard bucket

◆ : Heavy duty bucket

⊙ : Rock bucket

 Applicable for materials with density of 2000kgf/m³ (3370lbf/yd³) or less

 Applicable for materials with density of 1600kgf/m³ (2700lbf/yd³) or less

 Applicable for materials with density of 1100kgf/m³ (1850lbf/yd³) or less