

1. Excavators

1.1 Standard machine

Zero tail



Mini



Crawler



Wheel



1.2 Special application

High chassis



Long reach



Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m³/yd³)
R16-9	MT L3E	12.5 / 16.8	1650/ 3640	0.04/ 0.05
R17Z-9A	KB D902	12.5 / 16.8	1700/ 3750	0.04/ 0.05
R25Z-9A	MT S3L2	18.4 / 24.7	2600/ 5730	0.07/ 0.09
R25Z-9AK	KB D1305	18.5 / 24.8	2580/ 5690	0.07/ 0.09
R27Z-9	MT S3L2	18.4 / 24.7	2730/ 6020	0.08/ 0.10
R30Z-9AK	KB D1305	18.5 / 24.8	3005/ 6620	0.08/ 0.10
R35Z-7	YM 3TNV88	20 / 27	3500/ 7720	0.11/ 0.14
R35Z-7A/9	YM 3TNV88-BSHYB	20.3 / 27.3	3650/ 8050	0.11/ 0.14
R35Z-9A	YM 3TNV88F-ESHYB	18.2/ 24.4	3690/ 8140	0.11/ 0.14
R55-7	YM 4TNV94L	39 / 52	5700/ 12570	0.07 ~ 0.18/ 0.09 ~ 0.24
R55-7A	YM 4TNV98-EPHYB	42.5 / 57	5700/ 12570	0.07 ~ 0.18/ 0.09 ~ 0.24
R55-9	YM 4TNV98-EPHYBU	42.5 / 57	5650/ 12460	0.07 ~ 0.18/ 0.09 ~ 0.24
R55-9A	YM 4TNV98C	49.9 / 66.9	5650/ 12460	0.07 ~ 0.18/ 0.09 ~ 0.24
R60-9S	YM 4TNV94L-XHYB2	39 / 52.3	5650/ 12460	0.07 ~ 0.18/ 0.09 ~ 0.24
R60CR-9	YM 4TNV98-EPHYBU	42.5 / 57.8	5900/ 13010	0.07 ~ 0.18/ 0.09 ~ 0.24
R60CR-9A	YM 4TNV98C-PHYB1	49.9 / 66.9	5900/ 13010	0.07 ~ 0.18/ 0.09 ~ 0.24
R80-7	YM 4TNV98	43 / 58	7800/ 17200	0.28 ~ 0.31/ 0.37 ~ 0.41
R80-7A	YM 4TNV98-ZVHYB	44.4 / 59.6	7800/ 17200	0.28 ~ 0.31/ 0.37 ~ 0.41
R80CR-9	YM 4TNV98-ZVHYB	45 / 60.4	8200/ 18080	0.28/ 0.37
R80CR-9A	YM 4TNV98C	49.9 / 66.9	8350/ 18410	0.28/ 0.37
R110-7	MT S4K-T	63 / 84	11900/ 26230	0.30 ~ 0.59/ 0.39 ~ 0.77
R110-7A	MT D04FD-TAA	72 / 97	11200/ 24690	0.30 ~ 0.59/ 0.39 ~ 0.77
R125LCR-9A	PK 1204E	74.3/ 100	12500/ 27560	0.40 ~ 0.45/ 0.52 ~ 0.59
R140LC-7	CM B3.9	76 / 102	13980/ 30820	0.22 ~ 0.70/ 0.26 ~ 0.92
R140LC-7A	MT D04FD-TAA	78 / 105	13980/ 30820	0.22 ~ 0.70/ 0.26 ~ 0.92
R140LC-9	MT D04FD-TAA	78 / 105	13980/ 30820	0.22 ~ 0.70/ 0.26 ~ 0.92
R140LC-9A	PK 1204E	92.5 / 124	13980/ 30820	0.23 ~ 0.71/ 0.30 ~ 0.93
R140LC-9S	CM B3.9	78 / 105	13980/ 30820	0.23 ~ 0.71/ 0.30 ~ 0.93
HX140 L	PK 1204F	92.6 / 124	14200/ 31310	0.23 ~ 0.71/ 0.30 ~ 0.93
R145CR-9	MT D04FD-TAA	89 / 119	14600/ 32190	0.23 ~ 0.71/ 0.30 ~ 0.93
R145CR-9A	PK 1204E	92.5 / 124	14600/ 32190	0.23 ~ 0.71/ 0.30 ~ 0.93
HX145 LCR	PK 1204F	92.6 / 124	14780/ 32580	0.23 ~ 0.71/ 0.30 ~ 0.93
R160LC-7	MT S6S-DT	87 / 116	17400/ 38360	0.39 ~ 1.05/ 0.51 ~ 1.37
R160LC-7A	MT D04FD-TAA	87 / 116	17400/ 38360	0.39 ~ 1.05/ 0.51 ~ 1.37
R160LC-9	MT D04FD-TAA	87 / 116	17800/ 39240	0.39 ~ 1.05/ 0.51 ~ 1.37
R160LC-9A	PK 1204E	102 / 137	17800/ 39240	0.39 ~ 0.89/ 0.51 ~ 1.16
R160LC-9S	MT S6S-DT	87 / 116	17800/ 39240	0.39 ~ 0.89/ 0.51 ~ 1.16
HX160 L	PK 1204F	102.1 / 137	18100/ 39900	0.39 ~ 1.05/ 0.51 ~ 1.37
R180LC-7	MT S6S-DT	87 / 116	18200/ 40120	0.39 ~ 1.05/ 0.51 ~ 1.37
R180LC-7A	MT D04FD-TAA	87 / 116	18200/ 40120	0.39 ~ 1.05/ 0.51 ~ 1.37
R180LC-9	MT D04FD-TAA	87 / 116	18600/ 41010	0.39 ~ 1.05/ 0.51 ~ 1.37
R180LC-9A	MT S6S-DT	94 / 126	18600/ 41010	0.39 ~ 1.05/ 0.51 ~ 1.37
R180LC-9S	MT S6S-DT	87 / 116	18600/ 41010	0.39 ~ 1.05/ 0.51 ~ 1.37
HX180 L	PK 1204F	102.1 / 137	18800/ 41450	0.39 ~ 1.05/ 0.51 ~ 1.37
R210LC-7	CM B5.9	107 / 143	21790/ 47840	0.51 ~ 1.34/ 0.67 ~ 1.75
R210LC-7(#98001-)	CM 6BTAA	112 / 150	21700/ 47840	0.52 ~ 1.20/ 0.67 ~ 1.57
R210LC-7A	CM QSB6.7	113 / 151	21900/ 48280	0.51 ~ 1.34/ 0.67 ~ 1.75
R210LC-7H	HD D6BV	107 / 143	21500/ 47400	0.51 ~ 1.34/ 0.67 ~ 1.75
R220LC-7H	HD D6BV	117 / 159	21500/ 47400	0.51 ~ 1.34/ 0.67 ~ 1.75
R210LC-7H(#9001-)	HD D6BT	103 / 137	21500/ 47400	0.52 ~ 1.20/ 0.67 ~ 1.57

Notes

Model - CM : Cummins

KB : Kubota

Engine - YM : Yanmar

HD : Hyundai

PK : Perkins

MT : Mitsubishi

1. Excavators

1.1 Standard machine

Zero tail



Mini



Crawler



Wheel



1.2 Special application

High chassis



Long reach



Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m³/yd³)
R210NLC-7	CM 6BTAA	112 / 150	22000/ 48500	0.51 ~ 1.34/ 0.67 ~ 1.75
R210NLC-7A	CM QSB6.7	112 / 150	22000/ 48500	0.51 ~ 1.34/ 0.67 ~ 1.75
R210LC-9	CM QSB6.7	113 / 151	21900/ 48280	0.51 ~ 1.34/ 0.67 ~ 1.75
R220LC-9A	CM QSB6.7	125 / 167	21900/ 48280	0.51 ~ 1.34/ 0.67 ~ 1.75
R220LC-9S	CM 6BTAA	112 / 150	21900/ 48280	0.51 ~ 1.34/ 0.67 ~ 1.75
R220LC-9SH	HD D6BV	107 / 145	21900/ 48280	0.51 ~ 1.34/ 0.67 ~ 1.75
R210NLC-9	CM QSB6.7	113 / 151	22000/ 48500	0.51 ~ 1.34/ 0.67 ~ 1.75
R220NLC-9A	CM QSB6.7	118 / 158	22000/ 48500	0.51 ~ 1.34/ 0.67 ~ 1.75
HX220 L	CM QSB 6.7	136 / 183	22100/ 48720	0.52 ~ 1.34/ 0.68 ~ 1.75
HX220 NL	CM QSB6.7	136 / 183	22300/ 49160	0.80 ~ 1.34/ 1.05 ~ 1.75
R235LCR-9	CM QSB6.7	113 / 151	23800/ 52470	0.51 ~ 1.34/ 0.67 ~ 1.75
R235LCR-9A	CM QSB6.7	125 / 167	23800/ 52470	0.51 ~ 1.34/ 0.67 ~ 1.75
HX235 LCR	CM QSB6.7	136 / 183	24000/ 52910	0.80/ 1.05
R250LC-7	CM B5.9	121 / 163	25200/ 55600	0.79 ~ 1.50/ 1.03 ~ 1.96
R250LC-7A	CM QSB6.7	121 / 163	25200/ 55600	0.60 ~ 1.50/ 0.78 ~ 1.96
R250LC-9	CM QSB6.7	137 / 183	25200/ 55600	0.60 ~ 1.50/ 0.78 ~ 1.96
R260LC-9A	CM QSB6.7	140 / 188	25200/ 55600	0.60 ~ 1.50/ 0.78 ~ 1.96
R260LC-9S	CM B5.9	133 / 178	25200/ 55600	0.60 ~ 1.50/ 0.78 ~ 1.96
HX260 L	CM QSB 6.7	142 / 190	25600/ 56440	1.08 ~ 1.50/ 1.41 ~ 1.96
R290LC-7	CM QSB	159 / 213	29300/ 64600	0.79 ~ 1.85/ 1.03 ~ 2.42
R290LC-7H	HD D6AZ	149 / 200	28800/ 63500	0.79 ~ 1.85/ 1.03 ~ 2.42
R290LC-7A	CM QSB 6.7	147 / 197	29300/ 64600	0.79 ~ 1.85/ 1.03 ~ 2.42
R290LC-9	CM QSB 6.7	147 / 197	29300/ 64600	0.79 ~ 1.85/ 1.03 ~ 2.42
R290LC-9MH	CM QSB6.7	169 / 227	32710/ 72110	*1.09/ 1.18
R300LC-7	HD D6AC	162 / 217	29600/ 65300	0.79 ~ 1.85/ 1.03 ~ 2.42
R300LC-9A	CM QSB6.7	168 / 225	29800/ 65700	0.79 ~ 1.85/ 1.03 ~ 2.42
R300LC-9S	CM C8.3	196 / 263	29700/ 65480	0.79 ~ 1.85/ 1.03 ~ 2.42
R300LC-9SH	HD D6AC	162 / 217	29900/ 65920	0.79 ~ 1.85/ 1.03 ~ 2.42
HX300 L	CM QSB 6.7	180 / 242	30200/ 66580	0.52 ~ 1.85/ 0.68 ~ 2.42
R305LC-7	CM C8.3	190 / 255	29300/ 64600	0.79 ~ 1.85/ 1.03 ~ 2.42
R320LC-7	CM C8.3	193 / 259	32200/ 70990	0.90 ~ 2.10/ 1.18 ~ 2.75
R320LC-7A	CM QSC	177 / 237	32200/ 71000	0.90 ~ 2.10/ 1.18 ~ 2.75
R320LC-9	CM QSC	196 / 263	32200/ 71000	0.90 ~ 2.10/ 1.18 ~ 2.75
R330LC-9A	CM QSL9	210 / 282	33000/ 72750	0.90 ~ 2.10/ 1.18 ~ 2.75
R330LC-9S	CM C8.3	193 / 259	32700/ 72090	0.90 ~ 2.10/ 1.18 ~ 2.75
R330LC-9SH	HD D6A	206 / 276	33000/ 72750	0.90 ~ 2.10/ 1.18 ~ 2.75
HX330 L	CM QSL 9	212 / 284	33500/ 73850	0.90 ~ 2.10/ 1.18 ~ 2.75
R360LC-7	CM QSC8.3	195 / 261	36100/ 79590	1.15 ~ 2.32/ 1.50 ~ 3.03
R360LC-7A	CM QSL	195 / 261	36100/ 79590	1.15 ~ 2.32/ 1.50 ~ 3.03
R370LC-7	HD D6AC	206 / 276	36900/ 81350	1.15 ~ 2.32/ 1.50 ~ 3.03
R380LC-9	CM QSL	202 / 271	38200/ 84220	1.15 ~ 2.32/ 1.50 ~ 3.03
R380LC-9MH	CM QSL	221 / 296	43240/ 95330	*1.20/ 1.57
R380LC-9DM	CM QSL	221 / 296	45420/ 100130	-
R380LC-9A	CM QSL9	231 / 310	38200/ 84220	1.46 ~ 2.32/ 1.91 ~ 3.03
R380LC-9SH	HD D6AC	206 / 276	38400/ 84660	1.46 ~ 2.32/ 1.91 ~ 3.03
HX380 L	CM QSL 9	236 / 316	38920/ 85800	1.46 ~ 2.32/ 1.91 ~ 3.03
R430LC-9	CM QSL	221 / 296	42600/ 93920	1.90 ~ 2.10/ 2.49 ~ 2.75
R430LC-9A	CM QSL9	231 / 310	42600/ 93920	1.90 ~ 2.10/ 2.49 ~ 2.75
R430LC-9SH	HD D6AC	206 / 276	42600/ 93920	1.90 ~ 2.10/ 2.49 ~ 2.75

Notes

Model - CM : Cummins

HD : Hyundai

Engine - YM : Yanmar

SC : Scania

*1 : Grapple

1. Excavators

1.1 Standard machine

Zero tail



Mini



Crawler



Wheel



1.2 Special application

High chassis



Long reach



Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (SAE, m³/yd³)
R450LC-7	CM QSM11	239 / 320	44900/ 99000	1.38 ~ 3.03/ 1.80 ~ 3.96
R450LC-7A	CM QSM11	266 / 357	45200/ 99650	1.38 ~ 3.03/ 1.80 ~ 3.96
R480LC-9	CM QSM11	266 / 357	48100/ 106040	1.00 ~ 3.03/ 1.30 ~ 3.96
R480LC-9MH	CM QSM11	266 / 357	55210/ 121720	*1.40/ 1.83
R480LC-9A	CM QSX11.9	277 / 372	48100/ 106040	1.00 ~ 3.03/ 1.31 ~ 3.96
R480LC-9S	CM QSM11	263 / 353	48100/ 106040	1.00 ~ 3.03/ 1.31 ~ 3.96
HX480 L	SC DC13	331 / 444	49500/ 109130	1.00 ~ 3.20/ 1.30 ~ 4.19
R500LC-7	CM QSM11	263 / 353	48800/ 107580	1.38 ~ 3.60/ 1.80 ~ 4.71
R500LC-7A	CM QSM11	266 / 357	48800/ 107580	1.38 ~ 3.60/ 1.80 ~ 4.71
R520LC-9	CM QSM11	266 / 357	51000/ 112430	1.00 ~ 3.20/ 1.30 ~ 4.19
R520LC-9A	CM QSX11.9	277 / 372	51000/ 112430	1.65 ~ 3.03/ 2.16 ~ 3.96
R520LC-9S	CM QSM11	263 / 353	51000/ 112430	1.65 ~ 3.03/ 2.16 ~ 3.96
HX520 L	SC DC13	331 / 444	52400/ 115520	1.00 ~ 3.20/ 1.30 ~ 4.19
R700LC-9	SC DC16 074A	405 / 550	72400/ 156610	3.30 ~ 4.60/ 4.32 ~ 6.02
R800LC-7A	CM QSB15	366 / 490	82320/ 181480	3.40 ~ 5.10/ 4.45 ~ 6.67
R800-7A FS	CM QSX15	366 / 490	86700/ 191140	4.50 ~ 5.10/ 5.89 ~ 6.60
R800LC-9	CM QSX15	380 / 510	83400/ 183860	2.56 ~ 5.10/ 3.35 ~ 6.60
R800LC-9 FS	CM QSX15	366 / 490	87800/ 193560	4.50/ 5.89
R1200LC-9	CM QSK23	567 / 760	118000/ 260140	6.70/ 8.76
R55W-7	YM 4TNV94L	42 / 57	5600/ 12350	0.07 ~ 0.18/ 0.09 ~ 0.24
R55W-7A	YM 4TNV98-EPHYB	42.5 / 57	5600/ 12350	0.07 ~ 0.18/ 0.09 ~ 0.24
R55W-9	YM 4TNV98-EPHYB	42.5 / 57	5550/ 12240	0.07 ~ 0.18/ 0.09 ~ 0.24
R55W-9A	YM 4TNV98C	50 / 70	5550/ 12240	0.07 ~ 0.18/ 0.09 ~ 0.24
R60W-9S	YM 4TNV94L-PHYBY	41.2 / 55	5550/ 12240	0.07 ~ 0.18/ 0.09 ~ 0.24
R140W-7	CM B3.9	86 / 115	13500/ 29760	0.23 ~ 0.71/ 0.30 ~ 0.93
R140W-7A	MT D04FD-TAA	89 / 119	13500/ 29760	0.23 ~ 0.71/ 0.30 ~ 0.93
R140W-9	CM QSB 6.7	107 / 143	13700/ 30200	0.23 ~ 0.71/ 0.30 ~ 0.93
R140W-9A	CM QSB 6.7	109 / 146	13700/ 30200	0.23 ~ 0.71/ 0.30 ~ 0.93
R140W-9S	CM B3.9	78 / 105	13700/ 30200	0.23 ~ 0.71/ 0.30 ~ 0.93
HW140	CM QSB 6.7	117 / 157	13880/ 30600	0.23 ~ 0.71/ 0.30 ~ 0.93
R160W-9A	CM QSB 6.7	123 / 165	16700/ 36820	0.39 ~ 0.89/ 0.51 ~ 1.16
HW160	CM QSB6.7	134 / 180	17100/ 37700	0.39 ~ 1.05/ 0.51 ~ 1.37
R170W-7	MT S6S-DT	94 / 126	16200/ 35710	0.39 ~ 1.05/ 1.51 ~ 1.37
R170W-7A	MT D04FD-TAA	94 / 126	16400/ 36160	0.39 ~ 1.05/ 1.51 ~ 1.37
R170W-9	CM QSB 6.7	122 / 163	17300/ 38140	0.39 ~ 1.05/ 1.51 ~ 1.37
R170W-9S	MT S6S-DT	94 / 128	17300/ 38140	0.39 ~ 1.05/ 1.51 ~ 1.37
R180W-9A	CM QSB 6.7	123 / 165	17280/ 38100	0.39 ~ 1.05/ 1.51 ~ 1.37
R180W-9S	MT S6S-DT	94 / 128	17300/ 38140	0.39 ~ 1.05/ 1.51 ~ 1.37
HW180	CM QSB6.7	134 / 180	17800/ 39240	0.39 ~ 1.05/ 0.51 ~ 1.37
R200W-7	CM B5.9	124 / 166	20500/ 45200	0.51 ~ 1.34/ 0.67 ~ 1.75
R200W-7A	CM QSB 6.7	122 / 164	20500/ 45200	0.51 ~ 1.34/ 0.67 ~ 1.75
R210W-9	CM QSB 6.7	131 / 176	20500/ 45200	0.51 ~ 1.34/ 0.67 ~ 1.75
R210W-9MH	CM QSB 6.7	131 / 176	25700/ 56660	*1.0.70/ 0.92
R210W-9A	CM QSB 6.7	129 / 173	20500/ 45200	0.51 ~ 1.34/ 0.67 ~ 1.75
R210W-9S	CM B5.9	124 / 166	20500/ 45200	0.51 ~ 1.34/ 0.67 ~ 1.75
HW210	CM QSB 6.7	137 / 183	21200/ 46740	0.80 ~ 1.34/ 1.05 ~ 1.75

Notes

Model - CM : Cummins

SC : Scania

Engine - YM : Yanmar

MT : Mitsubishi

*1 : Grapple

2. Wheel loaders



TM machine




757TM7PL1PG9-10

Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (m³/yd³)
HL730-7	CM B3.9	93 / 125	9700/ 21390	1.60 ~ 2.10/ 2.10 ~ 2.70
HL730-7A	CM QSB4.5	89 / 119	9700/ 21390	1.60 ~ 2.10/ 2.10 ~ 2.70
HL730TM-7	CM B3.9	93 / 125	10000/ 22050	1.40 ~ 1.90/ 1.80 ~ 2.50
HL730TM-7A	CM QSB4.5	93 / 125	10000/ 22050	1.40 ~ 1.90/ 1.80 ~ 2.50
HL730-9	CM QSB4.5	93 / 125	9800/ 21600	1.70 ~ 2.40/ 2.22 ~ 3.14
HL730-9A	CM QSB4.5	97 / 130	10500/ 23150	1.70 ~ 2.40/ 2.22 ~ 3.14
HL730-9S	CM QSB4.5	93 / 125	9700/ 21400	1.70 ~ 2.40/ 2.22 ~ 3.14
HL730TM-9	CM QSB4.5	93 / 125	10200/ 22490	1.40 ~ 1.90/ 1.80 ~ 2.50
HL730TM-9A	CM QSB4.5	97 / 130	10900/ 24030	1.40 ~ 1.90/ 1.80 ~ 2.50
HL740-7	CM QSB5.9	104 / 140	11500/ 25350	1.70 ~ 2.30/ 2.20 ~ 3.00
HL740-7S	CM 6BTA5.9	112 / 150	10500/ 23100 10730/ 23650	1.70 ~ 2.30/ 2.20 ~ 3.00
HL740-7A	CM QSB6.7	108 / 145	11550/ 25460	1.70 ~ 2.30/ 2.20 ~ 3.00
HL740TM-7	CM QSB5.9	104 / 140	12050/ 26570	1.70 ~ 2.00/ 2.20 ~ 2.60
HL740TM-7A	CM QSB6.7	108 / 145	12100/ 26700	1.70 ~ 2.00/ 2.20 ~ 2.60
HL740-9	CM QSB6.7	108 / 145	12000/ 26460	2.00 ~ 2.80/ 2.60 ~ 3.70
HL740-9A	CM QSB6.7	118 / 158	12700/ 28000	2.00 ~ 2.80/ 2.60 ~ 3.70
HL740-9S	CM 6BTA5.9	112 / 150	11550/ 25460	2.00 ~ 2.80/ 2.60 ~ 3.70
HL740TM-9	CM QSB6.7	108 / 145	12600/ 27780	2.00 ~ 2.50/ 2.60 ~ 3.30
HL740TM-9A	CM QSB6.7	118 / 158	13300/ 29320	2.00 ~ 2.50/ 2.60 ~ 3.30
HL757-7	CM QSB5.9	129 / 173	13800/ 30420	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757-7S	CM 6BTA5.9	123 / 165	13000/ 28600 13180/ 29100	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757-7A	CM QSB6.7	129 / 173	14500/ 31970	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757TM-7	CM QSB5.9	129 / 173	14300/ 31530	2.30 ~ 2.70/ 3.00 ~ 3.50
HL757TM-7A	CM QSB6.7	129 / 173	15000/ 33070	2.30 ~ 2.70/ 3.00 ~ 3.50
HL757-9	CM QSB6.7	127 / 170	14500/ 32000	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757-9A	CM QSB6.7	149 / 200	14700/ 32400	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757TM-9	CM QSB6.7	129 / 173	15000/ 33070	2.30 ~ 2.70/ 3.00 ~ 3.50
HL757TM-9A	CM QSB6.7	149 / 200	15200/ 33500	2.30 ~ 2.70/ 3.00 ~ 3.50
HL757-9S	CM QSB6.7	127 / 170	14000/ 30860	2.30 ~ 3.20/ 3.00 ~ 4.20
HL757-9SM	CM 6BTAA5.9	129 / 173	13600/ 30000	2.30 ~ 3.20/ 3.00 ~ 4.20
HL760-7	CM QSB5.9	160 / 215	17900/ 39460	2.50 ~ 4.00/ 3.30 ~ 5.20
HL760-7A	CM QSB6.7	160 / 215	17900/ 39460	2.50 ~ 4.00/ 3.30 ~ 5.20
HL760-9	CM QSB6.7	153 / 205	17900/ 39460	2.50 ~ 4.00/ 3.30 ~ 5.20
HL760-9A	CM QSB6.7	166 / 222	18350/ 40450	2.50 ~ 4.00/ 3.30 ~ 5.20
HL760-9S	CM 6CTAA8.3	153 / 205	17600/ 38800	2.50 ~ 4.00/ 3.30 ~ 5.20
HL770-7	CM QSC8.3	206 / 276	22800/ 50270	3.30 ~ 4.30/ 4.32 ~ 5.60
HL770-7A	CM QSL	209 / 280	23100/ 50930	3.30 ~ 4.30/ 4.32 ~ 5.60
HL770-9	CM QSL	209 / 280	23100/ 50930	3.30 ~ 5.00/ 4.32 ~ 6.50
HL770-9A	CM QSL9	224 / 300	23500/ 51810	3.30 ~ 5.00/ 4.32 ~ 6.50
HL770-9S	CM QSL	209 / 280	22500/ 49600	3.30 ~ 5.00/ 4.32 ~ 6.50
HL780-7A	CM QSM11	250 / 335	29300/ 64600	4.20 ~ 5.50/ 5.20 ~ 7.20
HL780-9	CM QSM11	260 / 348	30000/ 66100	4.20 ~ 5.50/ 5.20 ~ 7.20
HL780-9A	CM QSM11.9	265 / 355	30300/ 66800	4.20 ~ 5.50/ 5.20 ~ 7.20
HL780-9S	CM QSM11	260 / 348	29500/ 65040	4.20 ~ 5.50/ 5.20 ~ 7.20
HL780-9S UMA	CM QSM11	260 / 348	32500/ 71650	5.40/ 7.10
HL940	CM QSB6.7	118 / 158	13100/ 28880	2.30/ 3.00
HL940TM	CM QSB6.7	118 / 158	13600/ 29980	2.30/ 3.00
HL955	CM QSB6.7	149 / 200	15100/ 33290	2.50/ 3.10
HL955TM	CM QSB6.7	149 / 200	15600/ 34390	2.70/ 3.50

CM : Cummins

2. Wheel loaders



TM machine



757TM7PL1PG9-10

Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (m³/yd³)
HL960	CM QSB6.7	168 / 225	18800 / 41450	2.80/ 3.70
HL970	SC DC09	232 / 311	23500 / 51810	3.60/ 4.20
HL975	CM QSG12	250/335	26500/58430	4.80/ 6.30
HL980	SC DC13	283 / 380	31000/ 68340	5.60/ 7.30
SL733	YC6J125Z-T20	92 / 123	10200/ 22490	1.80/ 2.40
SL733S	YC6J125Z-T20	92 / 123	10200/ 22490	1.70/ 2.20
SL735	YC6J125Z-T20	92 / 123	10200/ 22490	1.80/ 2.40
SL760	WP WD10G220E2	162 / 217	17100/ 37700	3.10/ 4.10
SL763	WP WD10G220E2	162 / 217	17100/ 37700	3.10/ 4.10
SL763S	WP WD10G220E23	162 / 217	16500/ 36380	3.00/ 3.90
SL765	WP WD10G220E23	162 / 217	16800/ 37040	3.10/ 4.10
SL765S	WP WD10G220E23	162 / 217	16500/ 36380	3.00/ 3.90

CM : Cummins

SC : Scania

WP : Weichai power

3. Skid steer loaders



6507APG01

Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (m³/yd³)
HSL610	YM 4TNE88	31 / 41	2350/ 5180	0.32 / 0.42
HSL810	YM 4TNE88	52 / 70	3260/ 7190	0.35 / 0.46
HSL650-7	KB V2203M	32 / 42.6	2625/ 5780	0.31 / 0.41
HSL650-7A	KB V2403M	34.3 / 46	2690/ 5930	0.31 / 0.41
HSL850-7	KB V3300DI	50 / 68	3290/ 7250	0.37 / 0.48
HSL850-7A	KB V3307-T	53.5 / 72	3290/ 7250	0.37 / 0.48

YM : Yanmar

KB : Kubota

4. Backhoe loaders



940CPL01

Model	Engine	Horse power (kW/hp)	Operating weight (kg/lb)	Bucket capacity (m³/yd³)
HB90	IC F4GE9454J*J	66 / 89	7830/ 17260	
HB100	IC F4GE9484F*J	74 / 99	7900/ 17420	
H930C	IC F4GE9454J*J	68.5 / 92	7830/ 17260	
H940C	IC F4GE9484F*J	74.5 / 100	7900/ 17420	
H930S	PK 1104C-44T	68.5 / 92	7830/ 17260	
H940S	PK 1104C-44T	74.5 / 100	7900/ 17420	

IC : Iveco

PK : Perkins